

# Material Safety Data Sheet

Company and Contact Information		
CAF, LLC PO Box 1121 Maple Valley, WA 98038 (425) 433-8277	<b>24-Hour Emergency Number: (800) 255-3924</b> CHEMTEL Contract Number: MIS0006822 Date Prepared: July 19, 2013. Date Revised:	Reorder Hotline: (425) 433-8277 email: <a href="mailto:sales@mycaf.com">sales@mycaf.com</a>

Identification – Section I	HMIS Rating
Product Name: Touch Up Custom Paint and Primer Chemical Family: Latex, water based Formula: N/A CAS Number: N/A	0-Minimal   1-Slight   2- Moderate   3- Serious   4-Extreme HEALTH: 1* FLAMMABILITY: 0 PHYSICAL HAZARD: 0 PERSONAL PROTECTION: A

Hazard Identification – Section II	
<b>Eyes:</b>	Irritation
<b>Skin (Dermal):</b>	Prolonged or repeated exposure may cause irritation
<b>Ingestion (Swallowing):</b>	May cause gastrointestinal irritation and discomfort
<b>Inhalation:</b>	Irritation of the upper respiratory system
<b>Chronic Overexposure:</b>	Redness and itching or burning sensation may indicate eye or excessive skin exposure
<b>Aggravated Conditions:</b>	None generally recognized

Ingredients – Section III			
Chemical Name/Common Name	CAS NO	PERCENT	TLV (Source)
Zinc Oxide	1314-13-2	2	10 mg/m3 as dust
Titanium Dioxide	13463-67-7	4	10 mg/m3 as dust
Crisobalite	14464-46-41	0.1	0.025 mg/m3 as dust

First-Aid Measures – Section IV	
<b>Eyes:</b>	Flush eyes with large amounts of water for at least 15 minutes. Get medical attention
<b>Skin (Dermal):</b>	Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use
<b>Ingestion (Swallowing):</b>	NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Inhalation:</b>	Remove to fresh air. Restore breathing. Keep warm and quiet

Fire-Fighting Measures – Section V		
Flash Point: N/A	LEL: N/A	UEL: N/A
Extinguishing Media: Use extinguishing media appropriate to primary cause of fire.		
Unusual Fire Hazards: During emergency conditions over exposure to decomposition product may cause a hazard.		
Special Fire Extinguishing Procedures: Full protective equipment including SCBA.		

Accidental Release Measures – Section VI	
Spill / Leak Procedures	Remove all sources of ignition. Ventilate area. Remove with inert absorbent

# Material Safety Data Sheet

## Handling and Storage – Section VII

Handling Information: KEEP OUT OF REACH OF CHILDREN.	Storage Requirements: Keep container closed when not in use. Transfer only to approved containers with appropriate labeling. Do not take internally
--	---

## Exposure Controls and Personal Protection – Section VIII

Respiratory Protection:	If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials listed in sec. 2
Ventilation Requirements:	Use outdoors or with adequate ventilation
Protective Gloves:	Recommended, but not required. Wash hands after using
Eye Protection:	Avoid contact with eyes. Use safety glasses
Notice: Removal of old paint by sanding, scraping or other means may generate hazardous dusts or fumes, including lead.	

## Physical and Chemical Properties – Section IX

Appearance: opaque, milky liquid	Vapor Density: Heavier than Air
Boiling Point: (F) 212 dF	Solubility in Water: Not available
PH: (1.0% solution) 8.8	VOC Theoretical – as packaged 0.39 lb/gal less water and Federally exempt solvents 0.13 lb/gal emitted VOC
Vapor Pressure: (mm/Hg): Not Est.      Evaporation Rate: slower than ether	

## Stability and Reactivity – Section X

Stability:	Stable
Incompatibility:	None known
Hazardous Decomposition:	By fire: carbon dioxide and carbon monoxide
Hazardous Polymerization:	Will not occur

## Toxicological Information – Section XI

Crystalline Silica	(Quartz, Cristobalite) is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.
Titanium Dioxide	IARC monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of product in which titanium is bound to other materials, such as paint."

## Ecological Information – Section XII

No data exists

## Disposal Considerations – Section XIII

Waste from this product is not hazardous as defined under RCA 40 CFR 261. Always consult all LOCAL, STATE, and FEDERAL regulations with regards to proper and suitable disposal method.

## Transportation and Storage Information – Section XIV

Proper Shipping Name:	N/A	Hazard Class:	N/A
UN Number	N/A	Hazard Label:	N/A

## Regulatory Information – Section XV

Listed Carcinogen:	California Proposition 65 – Warning: This product contains chemicals known to the State of California to cause cancer and birth defects and other reproductive harm.
TSCA Status:	All components in this product are listed on the TSCA inventory or are exempt from listing.
SARA Section 313:	Zinc Compound; 2% by wt., 1.7% by element.

## Other Information – Section XVI

References: The information contained herein is based on data available and is believed to be accurate. However, no warranty is expressed or implied regarding the accuracy of this data.